

THE SANSIN CORPORATION

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION AND USE

Page 1 of 2

PRODUCT IDENTIFIER SANSIN WOOD SEALER		PRODUCT IDENTIFICATION NUMBER (PIN) N/AP	
PRODUCT USE WATER REPELLENT			
MANUFACTURER'S NAME THE SANSIN CORPORATION.		SUPPLIERS NAME	
STREET ADDRESS 111 MACNAB AVENUE		STREET ADDRESS	
CITY STRATHROY	PROVINCE ON	CITY	PROVINCE
POSTAL CODE N7G 4J6	EMERGENCY TELEPHONE.NO: CANUTEC 613-996-6666	POSTAL CODE	EMERGENCY TELEPHONE #: US/NORTH AMERICA: 800-424-9300 OUTSIDE THE US: 703-527-3887

SECTION 2: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	CAS NUMBER	LD50 OF INGREDIENT (SPECIFY SPECIES AND ROUTE)	LC50 OF INGREDIENT (SPECIFY SPECIES)
ORGANIC CARBOXYLATE	< 8	N/AV	N/AV	N/AV
ZIRCONIUM COMPLEX	< 5	N/AV	N / AV	N / AV
3-IODO-2 PROPYNYL BUTYL CARBAMATE	0.2-0.5	55406-53-6		

SECTION 3: PHYSICAL DATA

PHYSICAL STATE LIQUID	ODOUR AND APPEARANCE SLIGHT AMMONIUM – OPAQUE WHITE			ODOUR TRESHOLD PPM N/AV
VAPOUR PRESSURE (MM HG) < 17.5	VAPOUR DENSITY (AIR=1) HEAVIER	EVAPORATION RATE N/AV	BOILING POINT 100°C . (212 ° F)	FREEZING POINT 0° C (32°F)
PH 9.3-9.7	SPECIFIC GRAVITY 1.0	COEFF. WATER/OIL DIST. MISCIBLE		

SECTION 4: FIRE AND EXPLOSION DATA

FLAMMABILITY YES (NO <input checked="" type="checkbox"/> IF YES, UNDER WHICH CONDITIONS			
MEANS OF EXTINCTION: NO RESTRICTIONS			
FLASHPOINT (°C) AND METHOD > 94°C (200°F)	UPPER FLAMMABLE LIMIT (% BY VOLUME)	N/AV	LOWER FLAMMABLE LIMIT (% BY VOLUME) :N/AV
AUTOIGNITION TEMPERATURE (°C) N/AV	HAZARDOUS COMBUSTION PRODUCTS N/AP		
EXPLOSION DATA	SENSITIVITY TO IMPACT N/AV	SENTIVITY TO STATIC DISCHARGE N/AV	

SECTION 5: REACTIVITY DATA

CHEMICAL STABILITY YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> IF NO, UNDER WHICH CONDITIONS	
INCOMPATIBILITY WITH OTHER SUBSTANCES : YES <input type="checkbox"/> NO <input type="checkbox"/> IF SO WHICH ONES: N/AV	
REACTIVITY, AND UNDER WHAT CONDITIONS FREEZING WILL DESTROY PRODUCT QUALITY	
HAZARDOUS DECOMPOSITION PRODUCTS NONE	

PRODUCT IDENTIFIER : SANSIN WOOD SEALER.

SECTION 6: TOXICOLOGICAL PROPERTIES

Page 2 of 2

ROUTE OF ENTRY: SKIN CONTACT <input checked="" type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE CONTACT <input checked="" type="checkbox"/> INHALATION <input checked="" type="checkbox"/> INGESTION <input checked="" type="checkbox"/>			
EFFECTS OF ACUTE EXPOSURE TO PRODUCT: N/AV			
EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: N/AV			
EXPOSURE LIMITS N/AV	IRRITANCY OF PRODUCT SKIN: IRRITATION EYES: IRRITATION	SENSITIZATION TO PRODUCT NONE KNOWN	CARCINOGENICITY NONE KNOWN
TERATOGENICITY NONE KNOWN	REPRODUCTIVE TOXICITY NONE KNOWN	MUTAGENICITY NONE KNOWN	SYNERGISTIC PRODUCTS NONE KNOWN

SECTION 7: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:			
GLOVES(SPECIFY) RUBBER, PVC	RESPIRATOR(SPECIFY) IF SPRAYING: NIOSH / MSHA APPROVED	EYE(SPECIFY) GOGGLES	
FOOTWEAR(SPECIFY) RUBBER, PVC	CLOTHING(SPECIFY) RUBBER APRON	OTHER(SPECIFY)	
ENGINEERING CONTROLS(SPECIFY,EG.VENTILATION, ENCLOSED PROCESS) : LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.'S			
LEAK AND SPILL PROCEDURE : CONTAIN SPREAD, SOAK UP WITH INERT ABSORBENT			
WASTE DISPOSAL : DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL & FEDERAL REGULATIONS			
HANDLING PROCEDURES AND EQUIPMENT : NO SPECIAL EQUIPMENT NEEDED			
STORAGE REQUIREMENTS : STORE IN DRY PLACE, DO NOT FREEZE, KEEP CONTAINER CLOSED			
SPECIAL SHIPPING INFORMATION : N/AP			

SECTION 8: FIRST AID MEASURES

SKIN : WASH WITH SOAP AND WATER, LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.
EYES : FLUSH WITH WATER FOR AT LEAST 20 MINUTES, LIFT UPPER AND LOWER LIDS
INHALATION: REMOVE TO FRESH AIR, IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. KEEP WARM AND AT REST.
INGESTION: DO NOT INDUCE VOMITING. KEEP WARM AND AT REST.
IN ALL CASES GET IMMEDIATE MEDICAL ATTENTION

SECTION 9: PREPARATION DATE OF MSDS

PREPARED BY :TECHNICAL DEPARTMENT	PHONE NUMBER (519) 245-4623	DATE JANUARY 2016
-----------------------------------	--------------------------------	----------------------

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of The Sansin Corporation's knowledge or is obtained from sources believed by The Sansin Corporation to be accurate. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests. Before using any products, read its label.