



Now you can put a great looking, high gloss Polyurethane finish on your floors and still use an environmentally friendly waterborne product! PolyOxide is designed specifically for tough applications like bar tops, residential or gymnasium floors, or even as a substitute for interior spar varnish, and it is an environmentally friendly waterborne finish! The secret is the micro-fine Aluminum Oxide particles added to the polyurethane and acrylic resins to increase durability without significantly affecting clarity.

This finish is very scuff resistant and resists attack from harsh chemicals like alcohol or household cleaners. Brush it on right out of the can with a synthetic brush or lambs wool applicator, or spray right out of the can with HVLP systems. Choose from three different finishes, satin, semi-gloss, and gloss. It is water clear and non-yellowing. UV stabilized great looks will keep the compliments coming. Cures hard overnight for next day move in. Easy to use and no lingering paint smell. Non-toxic and nonflammable. Meets or exceeds all Federal and State regulations (low VOC).

To use: Stir contents gently but thoroughly. Do not shake. Apply 3-5 coats allowing 2 hours drying time between coats. Hand-sand after first coat. Dries to touch in 30 minutes, cures hard in 24 hours - Ready for service. PolyOxide Wood Floor finish can be applied over any clean sanded surface, and is compatible with thoroughly dried oil or water based stain. Recommended for highlighting wood grain beauty.

- ✓ Chemical Resistant
- ✓ Fast Drying
- ✓ High Solids

- ✓ No Lingering Paint Smell
- ✓ Non-Flammable
- ✓ Non-Yellowing

- ✓ Scuff Resistant
- ✓ UV Stabilized
- ✓ Water Clean Up



Schroeder
Log Home Supply, Inc.

1-800-359-6614 www.loghelp.com