

SEALTITE 60

PRODUCT DESCRIPTION

For effective control of end checking and splitting during seasonal periods at economical cost, the especially fine solid particles in this free-flowing emulsion offer highly uniform coverage of the end grain, preventing rapid and uneven loss of moisture which is responsible for the physical stresses set up in seasoning wood.

DIRECTIONS FOR USE

Apply product as furnished without dilution. Brush, swab, or low pressure spray may be employed. For best results, end surfaces must be thoroughly covered by the coating. Rougher end grain will take more coating per square foot than finer end grain, and coverage will vary. About 100 square feet per gallon may be expected. If spray method is used, overatomization should be avoided as this might lead to evaporation causing the solids to be deposited in dry form. Do not apply to wood during a rain or just before a rain or where water will wash the wet coating. Allow to dry before exposure to water.

FIRST AID

IF IN EYES: Flush eyes with plenty of water. Call a physician if irritation persists.

IF ON SKIN: Wash exposed area with plenty of soap and water. If irritation persists, get medical attention.

If any unusual symptoms develop following ingestion or inhalation of this product, get medical attention.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants that this material conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use and Buyer assumes the risk of any use contrary to such directions. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO EXCEPT IN WRITING WITH A SPECIFIC REFERENCE TO THIS WARRANTY. In no event shall Seller's liability for any breach of warranty exceed the purchase price of the material as to which a claim is made.

STORAGE AND DISPOSAL

Store in a secure, well-ventilated area protected from extreme temperatures. Keep container closed when not in use. Absorb any spilled material with sand or clay and place in a waste receptacle. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Protect from temperatures below 20°F. DO NOT ALLOW TO FREEZE.

NOTE: Colored Sealtite 60 contains pigments which impart color. These pigments are in a finely divided suspension which may tend to settle during prolonged storage. If color of product does not seem to be as intense as usual, stir contents to insure uniform distribution of pigments.