



LOG-GEVITY™ INTERIOR GRADE FINISH COAT PRODUCT SPECIFICATIONS

PRODUCT NAME LOG-GEVITY™ INTERIOR GRADE FINISH COAT

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Log-Gevity™ Interior Grade Finish Coat is a low VOC product formulated with essential wood protecting ingredients blended in a deep penetrating oil. **Log-Gevity™ Interior Grade Finish Coat** is designed to provide a rich warm glow and natural wood finish. This non-film forming and breathable finish will provide years of color fastness to your interior log home investment. **Log-Gevity™ Interior Grade Finish Coat** is compatible with all **Log-Gevity™ Chinking** and most other **Log-Gevity™** products. It is also resistant to most cleaning solutions.

Log-Gevity™ Interior Grade Finish Coat is for use on all interior vertical log/wood surfaces susceptible to moisture damage, including all types of dimensional lumber.

Precautions: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards.

Fully protect all adjacent surfaces as well as general work area. When spraying near vegetation, cover plant life with cardboard or other suitable material in case of overspray.

TECHNICAL DATA

VOC Content Limit: Less than 250 grams per liter.

Packaging: One and five gallon containers.

Coverage: Approximately 200 sq. ft. per gallon.

FOR BEST RESULTS AND OPTIMAL PENETRATION: SURFACE MUST BE DRY DURING APPLICATION. BOTH SURFACE AND AIR TEMPERATURE MUST BE ABOVE 50°F.

PROPER SURFACE PREPARATION

IF YOU HAVE NEW OR OLD, DIRTY OR WEATHERED LOGS/WOOD

1. Clean logs/wood with **Log-Gevity™ New Log Prep** or other **Log-Gevity™ Product**.
2. If color is desired, select from a wide variety of pre-mixed, ready-to-use **Log-Gevity™ Interior Grade Finish Coat** transparent and solid color stains.
3. Apply a coat of **Log-Gevity™ Interior Grade Finish Coat**.
4. Apply **Log-Gevity™ Log Chinking** anytime after the interior finish coat has been applied and cured.

A second coat of **Log-Gevity™ Interior**

Grade Finish Coat will provide an extended color fastness and a semi-gloss finish.

Follow the complete **Log-Gevity™** product specification sheets for detailed instructions.

GENERAL DIRECTIONS

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Mix **Log-Gevity™ Interior Grade Finish Coat** well before using. A test area should be performed before beginning overall project to determine the amount of **Log-Gevity™ Interior Grade Finish Coat** the wood will absorb, dry time, wood porosity and total desired look.

For lumber that is not dried or seasoned: **Log-Gevity™ Interior Grade Finish Coat** is formulated to protect wood. However, the duration of protection will be in direct relationship to how much **Log-Gevity™ Interior Grade Finish Coat** has been absorbed into the wood. That is, the greater the dampness of the wood the less amount of absorption.

APPLICATION

1. Apply a coat of **Log-Gevity™ Interior Grade Finish Coat** with a low pressure (HVLP) sprayer or airless sprayer. When using a low pressure sprayer, always back brush into surface.
2. After the first coat has flash dried, which may take 30 minutes or longer, it may be necessary to apply a second coat of **Log-Gevity™ Interior Grade Finish Coat** for a

uniform effect.

3. To avoid runs and streaking, back brush product from surfaces before drying. Rough sawn wood will generally absorb more product evenly; however, it will still require back brushing.

4. Keep a wet edge to avoid lap marks.

DRY TIME: Allow at least 24 hours to dry.

CLEAN UP: Use mineral spirits or dish detergent and water. Should **Log-Gevity™ Interior Grade Finish Coat** come in contact with surfaces such as glass, paint, metal, caulking or rubber, remove immediately with dish detergent. If a spill is dry, clean it with mineral spirits.

DISPOSAL: Do not reuse empty can. Wrap can and place in trash. Leaking or damaged containers should be placed in a plastic bag and discarded. Contact local, state or federal agencies to ensure compliance of proper disposal methods and respective regulations.

STORAGE: Keep container closed when not in use. Store in cool place. This product should be kept out of reach of children and stored away from food. This product should always be stored in the original container in which it was purchased.

NOTICE: The information and recommendations made herein are based on **ABRP, Inc.**, research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because **ABRP, Inc.**, cannot anticipate every possible application of **ABRP, Inc.**, products, nor anticipate every variation encountered in

project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of **ABRP, Inc.**, products are not intended as recommendation to use **ABRP, Inc.**, products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed or implied, including without limitation warranties as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to the purchaser. This warranty gives the purchaser specific legal rights as well as other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications and brochures are available upon request.

Visit **www.Log-Gevity.com** for additional information regarding log home restoration and preservation products.

For more information on many of the specialty building restoration products available from **ABRP, Inc.**, please visit **www.abrp.com** or e-mail **ABRP, Inc.** at **support@abrp.com**.

© COPYRIGHT 2005 ABR PRODUCTS, INC.