

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label:

LIFELINE Wood Renew Product Name:

Other means of identification:

Recommended use of the chemical and restrictions on use:

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}$

Manufacturer Name: Perma-Chink Systems, Inc.

Address: 1605 Prosser Road Knoxville, TN 37914

Website: www.permachink.com General Phone Number: 800-548-3554 General Fax Number: 865-523-9475 Customer Service Phone Number: 865-524-7343

Emergency phone number:

Emergency Phone Number: CHEMTREC 1-800-424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:

Signal Word: DANGER.

GHS Class: Serious Eye Damage. Category 1.

Skin corrosion. Category 1. Acute Oral Toxicity. Category 4.

Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3 (RESP. IRR.).

Hazard Statements:

H318 - Causes serious eye damage. H314 - Causes severe skin burns and eye damage. H302 - Harmful if swallowed. H335 - May cause respiratory irritation.

Precautionary Statements: P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do not induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/shower.

Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P321 - Specific treatment (see ... on this label).
P330 - Rinse mouth.
P363 - Wash contaminated clothing before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

<u>Hazards not otherwise classified that have been identified during the classification process:</u>

Potential Health Effects:

Corrosive. Will cause eve burns and permanent tissue damage. Eve:

Skin: Severely irritating; may cause permanent skin damage.

Inhalation: May cause severe respiratory system irritation.

Ingestion: Harmful if swallowed. Corrosive to the gastrointestinal tract.

Chronic Health Effects: Prolonged skin contact causes burns.

> Product Code: Cor_Template LIFELINE Wood Renew Revision:: 11/02/2015

Repeated or prolonged inhalation may cause toxic effects.

Signs/Symptoms: Depending on solution concentration, material may be corrosive to skin, mucous membranes and

eyes. Vapors may cause respiratory irritation.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Conditions:

May aggravate pre-existing respiratory disorders, allergy, eczema, or skin conditions.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
Sodium Carbonate Peroxyhydrate	15630-89-4	70 - 80 by weight	239-707-6
Sodium acetate	127-09-3	0.1 - 0.5 by weight	204-823-8

SECTION 4: FIRST AID MEASURES

Description of necessary measures:

 $Immediately \ flush \ eyes \ with \ plenty \ of \ water for \ at \ least \ 15 \ to \ 20 \ minutes. \ Ensure \ adequate \ flushing \ of \ water \ for \ at \ least \ 15 \ to \ 20 \ minutes.$ Eve Contact:

the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing

contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention.

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give Ingestion:

anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

3

1

NFPA Ratings:

NFPA Health:

 $NFPA\ Flam mability:$

NFPA Reactivity: 2



SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use

proper personal protective equipment as listed in Section 8.

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by Methods for containment:

covering, diking or other means. Provide ventilation.

Methods for cleanup: Clean up spills immediately observing precautions in the protective equipment section. Provide

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Corrosive. Use proper personal protective equipment as listed in section 8. Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Wash hands thoroughly

> Product Code: Cor_Template LIFELINE Wood Renew Revision:: 11/02/2015

after handling.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Storage:

Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use. Keep only in the original, corrosive resistant container and store locked up.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Appropriate engineering controls:

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other

engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance

of the personal protective equipment.

Individual protection measures:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye

and face protection regulation, or the European standard EN 166.

 $Chemical-resistant\ gloves\ and\ chemical\ goggles,\ face-shield\ and\ synthetic\ apron\ or\ coveralls\ should\ be\ used\ to\ prevent\ contact\ with\ eyes,\ skin\ or\ clothing.$ Skin Protection Description:

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

shower.

PPE Pictograms:



SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Solid Physical State Appearance: Solid. Color White Odor Threshold: No Data

Boiling Point: Not applicable.

Melting Point: No Data

Density: 9.5 - 10.0 lb./gal

1.14 - 1.19 Specific Gravity: Solubility: < 150 g/L Vapor Density: Not applicable. Vapor Pressure: Not applicable.

Evaporation Rate: Not applicable. pH: Not applicable.

Molecular Formula:

Viscosity: Not applicable. Coefficient of Water/Oil Not applicable.

Flammability: No Data Flash Point: No Data

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable.

Oxidizing Properties: Oxidizer, Oxidizing Agent

VOC Content: No Data

SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Distribution:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, freezing or temperatures below 32 deg. F.

<u>Incompatible Materials:</u>

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Sodium Carbonate Peroxyhydrate:

Oral - Rat LD50 - Lethal dose, 50 percent kill: 2400 mg/kg [Behavioral - Somnolence (general Inaestion:

Oral - Rat LD50 - Lethal dose, 50 percent kill: 2400 mg/kg [Benavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 2400 mg/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lungs, Thorax, or Respiration - Respiratory depression]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 2400 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Respiratory depression] (RTECS)

Sodium acetate:

 $Inhalation - Rat\ LC50 - Lethal\ concentration,\ 50\ percent\ kill: > 30000\ mg/m3/1H\ [Details\ of\ toxic\ effects\ not\ reported\ other\ than\ lethal\ dose\ value]\ (RTECS)$ Inhalation:

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 3530 mg/kg [Details of toxic effects not reported other

than lethal dose value] (RTECS)

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

<u>Description of waste:</u>

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous Waste Disposal: waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

quidelines.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Paint Related Material.

DOT UN Number: UN3066 DOT Hazard Class: 8

DOT Packing Group: Π

DOT Exemption: Not applicable.

IATA Shipping Name: Paint Related Material.

IATA UN Number: 3066 IATA Hazard Class: 8 TT IATA Packing Group:

Canadian Shipping Name: Paint Related Material.

Canadian UN Number: 3066 Canadian Hazard Class: 8 Canadian Packing Group: TT IMDG UN Number: 3066

IMDG Shipping Name : Paint Related Material.

IMDG Hazard Class: 8 IMDG Packing Group: Π ADR UN Number: 3066

ADR Shipping Name: Paint Related Material.

> LIFELINE Wood Renew Product Code: Cor_Template

Revision:: 11/02/2015

ADR Hazard Class: 8

ADR Packing Group: II

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

Sodium Carbonate Peroxyhydrate:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 239-707-6

Sodium acetate:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 204-823-8

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 3
HMIS Fire Hazard: 1
HMIS Reactivity: 2
HMIS Personal Protection: X

Health Hazard	3
Fire Hazard	1
Reactivity	2
Personal Protection	х

SDS Creation Date: July 30, 2015
SDS Revision Date: November 02, 2015

SDS Format:

MSDS Author: Actio Corporation

Disclaimer: The information

The information contained herein is, to the best of Perma-Chink Systems, Inc. knowledge, accurate as of the data indicated. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that

he assumes the risk of his use thereof.

 $\label{local_conversion} \mbox{Copyright} \\ \mbox{\o 1996-2015 Actio Corporation. All Rights Reserved.}$

LIFELINE Wood Renew Revision:: 11/02/2015 Product Code: Cor_Template