

### SAFETY DATA SHEET

# SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: Woodsman™

Other means of identification:

Recommended use of the chemical and restrictions on use:

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}\\$ 

Manufacturer Name: Perma-Chink Systems, Inc.

Address: 1605 Prosser Road Knoxville, TN 37914

Website: www.permachink.com 800-548-3554 General Phone Number: General Fax Number: 865-523-9475 865-524-7343 Customer Service Phone Number:

Emergency phone number:

Emergency Phone Number: CHEMTREC 1-800-424-9300

# SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:

Signal Word: WARNING.

GHS Class:

Eye Irritation. Category 2. Hazardous to the aquatic environment, long-term, chronic. Category 3.

Hazard Statements: H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements:

P264 - Wash hands thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

 $\underline{\text{Hazards not otherwise classified that have been identified during the classification process:} \\$ 

Potential Health Effects:

Eye: Causes eye irritation. Skin: Causes skin irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation. Signs/Symptoms: Overexposure may cause headaches and dizziness. Target Organs: Eyes. Skin. Respiratory system. Digestive system.

None generally recognized. Aggravation of Pre-Existing

Conditions:

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

**Chemical Name** CAS# **Ingredient Percent** EC Num.

> Woodsman™ Product Code: NC-Template Revision:: 11/02/2015

Crystalline Silica, Quartz	14808-60-7	0.1 - 0.5 by weight	238-878-4
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	0.1 - 0.5 by weight	265-169-7
Solvent naphtha (pet), medium aliphatic.	64742-88-7	1 - 2 by weight	265-191-7
Titanium dioxide	13463-67-7	1 - 5 by weight	236-675-5
Isopropyl alcohol	67-63-0	2 - 3 by weight	200-661-7
Limestone	1317-65-3	30 - 40 by weight	215-279-6

#### SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. ContinueEye Contact:

rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give Ingestion:

anything by mouth to an unconscious person

# SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

Special protective equipment and precautions for fire-fighters:

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) Protective Equipment:

and full protective gear.

NFPA Ratings:

NFPA Health: 1 NFPA Flammability: 1

NFPA Reactivity:



# SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use

proper personal protective equipment as listed in Section 8.

**Environmental precautions:** 

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Methods for containment: Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by

covering, diking or other means. Provide ventilation.

Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water Methods for cleanup:

to remove trace residue

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use. Storage:

# SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Woodsman™ Revision:: 11/02/2015 Product Code: NC-Template

#### **EXPOSURE GUIDELINES:**

Crystalline Silica, Quartz:

Guideline ACGIH: TLV-TWA: 0.025 mg/m3 (R)

<u>Titanium dioxide</u>:

Guideline ACGIH: TLV-TWA: 10 mg/m3

Isopropyl alcohol:

TLV-STEL: 400 ppm TLV-TWA: 200 ppm Guideline ACGIH: Guideline OSHA: PEL-TWA: 400 ppm

Appropriate engineering controls:

Engineering Controls:

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Individual protection measures:

Eve/Face Protection:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

Skin Protection Description:

 $Chemical-resistant\ gloves\ and\ chemical\ goggles,\ face-shield\ and\ synthetic\ apron\ or\ coveralls\ should\ be\ used\ to\ prevent\ contact\ with\ eyes,\ skin\ or\ clothing.$ 

Respiratory Protection:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

PPE Pictograms:



#### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Paste. Physical State Appearance: Paste.

Color: Various Colors. Slight latex odor Odor:

**Boiling Point:** No Data Melting Point: No Data

9.80 - 10.20 lb./gal Density:

Specific Gravity: 1.18 - 1.22 Vapor Density: No Data Vapor Pressure: No Data Percent Volatile: 25-35 pH: 7.5 - 8.1 Molecular Formula: Mixture

275.000 - 325.000 cP Viscosity:

Flammability: No Data Flash Point: No Data Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable.

VOC Content: < 200 g/L (Regulatory Less Water)

## SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials:

Incompatible Materials Oxidizing agents. Strong acids and alkalis.

> Woodsman™ Product Code: NC-Template Revision:: 11/02/2015

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### TOXICOLOGICAL INFORMATION:

Crystalline Silica, Quartz:

Chronic Effects: Normal application procedures for this product pose no hazard as to the release of crystalline silica dust, but grinding or sanding dried films of this product may yield some respirable crystalline silica.

Carcinogenicity: Crystalline silica in the form of quartz or cristobalite dust causes cancer of the lung.

Petroleum distillates, solvent dewaxed heavy paraffinic:

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >5000 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: >5000 mg/kg [Details of toxic effects not reported other Ingestion:

than lethal dose value] (RTECS)

Titanium dioxide:

Normal application procedures for this product pose no hazard as to the release of respirable titanium dioxide dust, but grinding or sanding dried films of this product may yield some respirable titanium Chronic Effects:

dioxide. Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials". OSHA does not regulate titanium dioxide as a carcinogen. However, under 29CFR 1910.1200 the SDS must convey the fact that titanium dioxide

is a potential carcinogen to rats.

Carcinogenicity: Animal evidence shows that high concentrations of pigment-grade (powdered) and ultrafine titanium

dioxide dust caused respiratory tract cancer in rats exposed by inhalation.

Isopropyl alcohol:

Skin:

Eve:

Administration into the eye - Rabbit Standard Draize test: 100 mg [Severe]
Administration into the eye - Rabbit Standard Draize test: 10 mg [Moderate]
Administration into the eye - Rabbit Standard Draize test: 100 mg/24H [Moderate] (RTECS)

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 12800 mg/kg [Details of

toxic effects not reported other than lethal dose value] (RTECS)

Inhalation: Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 16000 ppm/8H [Details of toxic effects

not reported other than lethal dose value]
Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 72600 mg/m3 [Behavioral - General anesthetic Lungs, Thorax, or Respiration - Other changes] (RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: 5045 mg/kg [Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Somnolence (general depressed activity)]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 5000 mg/kg [Behavioral - General anesthetic] (RTECS) Ingestion:

### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

#### SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous

waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

### SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not restricted as a dangerous good.

DOT UN Number: Not restricted as a dangerous good.

IATA Shipping Name: Not restricted as a dangerous good.

IATA UN Number: Not restricted as a dangerous good.

Canadian Shipping Name: Not restricted as a dangerous good.

Canadian UN Number: Not restricted as a dangerous good.

IMDG UN Number: Not restricted as a dangerous good.

IMDG Shipping Name : Not restricted as a dangerous good.

ADR UN Number: Not restricted as a dangerous good.

ADR Shipping Name: Not restricted as a dangerous good.

> Woodsman™ Product Code: NC-Template Revision:: 11/02/2015

Page 4 of 5

# SECTION 15: REGULATORY INFORMATION

 $\underline{\textbf{Safety, health and environmental regulations specific for the product:}}$ 

265-191-7

Crystalline Silica, Quartz:

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 238-878-4

Petroleum distillates, solvent dewaxed heavy paraffinic :

TSCA Inventory Status: Listed Canada DSL: Listed 265-169-7 EC Number: Solvent naphtha (pet), medium aliphatic. :

TSCA Inventory Status: Listed Canada DSL: Listed

Titanium dioxide:

EC Number:

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 236-675-5

Isopropyl alcohol:

TSCA Inventory Status: Listed

Section 313:  $\ensuremath{\mathsf{EPCRA}}$  - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

Canada DSL: Listed 200-661-7 EC Number:

<u>Limestone</u>:

TSCA Inventory Status: Listed EC Number: 215-279-6

# SECTION 16: ADDITIONAL INFORMATION

**HMIS Ratings**:

HMIS Health Hazard: 1 HMIS Fire Hazard: 1 HMIS Reactivity: 0 HMIS Personal Protection: Χ

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	х

Page 5 of 5

July 30, 2015 SDS Creation Date: SDS Revision Date: November 02, 2015

SDS Format:

MSDS Author: Actio Corporation

Disclaimer:

The information contained herein is, to the best of Perma-Chink Systems, Inc. knowledge, accurate as of the data indicated. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assumes the risk of his use thereof.

Copyright@ 1996-2015 Actio Corporation. All Rights Reserved.

Woodsman™ Product Code: NC-Template