



Product Specifications

Product Name: Super Bio Strip™

Manufacturer: American Building Restoration Products, Inc.



PRODUCT DESCRIPTION: Super Bio Strip™ is a water soluble, multi purpose stripper and cleaner. The Super Bio Strip™ product line is biodegradable, non-flammable and contains no methylene chloride. Super Bio Strip™ is formulated in two viscosities: liquid and gel. Use liquid for easy to strip or clean surfaces, gel for more difficult tasks. Super Bio Strip™ removes a wide variety of paints, organic finishes, stains, graffiti and varnishes from both exterior and interior surfaces of wood, metal, masonry, fiberglass and marine surfaces. Super Bio Strip™ requires no neutralizing. Super Bio Strip™ Gel dwells longer, providing deeper penetration on multiple layers of paint and allows the applicator to work on surfaces with heavy accumulations of paint.

PRECAUTIONS: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces, as well as floor and general work area, from coming into direct contact with Super Bio Strip™.

CAUTION: On glass surfaces, all Super Bio Strip™ overspray and/or residue from the stripping process must be immediately removed to avoid adherence to the glass surface.

TECHNICAL DATA COLOR/FORM: Reddish-brown liquid/gel.

COVERAGE: Super Bio Strip™ Gel: 50-100 sq. ft. per gallon, depending on layers of paint to strip. Super Bio Strip™ Liquid: 50-150 sq. ft. per gallon.

PACKAGING: One, five and fifty-five gallon containers.

INSTALLATION PREPARATORY WORK: Prepare a surface free from dirt and oil. It is not necessary to remove loose, peeling or flaking paint. This creates pockets down to the surface which is generally more absorbing than the painted surface. A test area should be performed prior to beginning overall project to determine optimum dwell time for the product to completely penetrate all layers of the finish. User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state, or federal disposal regulations when using the product.

APPLICATION: 1. Using a brush, roller, low pressure sprayer or airless paint sprayer, apply a thick coat of Super Bio Strip™ to surface.

CAUTION: Super Bio Strip™ is slippery when applied to surface. Use extreme caution when working on horizontal surfaces. 2. Allow Super Bio Strip™ to remain on the surface until finish has dissolved. To prevent premature rinsing, wait for the entire surface to become uniformly darkened. This darkened appearance indicates that the Super Bio Strip™ has dissolved the underlying finish and is ready to be rinsed. 3. Reapply Super Bio Strip™ if necessary. 4. When used as a refinisher, saturate a pad of steel wool and remove finish by scrubbing with the grain. Rinse pad occasionally with water.

REMOVAL: 1. Scrape all dissolved residue and discard in an appropriate container. 2. If wood has become discolored, leave a solution of X-180 Weathered Wood Restorer™ on the discolored area until a crystallized residue appears. Lightly remove crystals from surface without destroying the brightening action of the X-180 Weathered Wood Restorer™ with a very light water rinse. 3. Certain types of wood surfaces may have a raised grain effect after stripping is completed. Very light sanding with 50 grit sandpaper where needed will smooth out this condition. Excessive sanding will close the wood grain, preventing the new finish from penetrating into the wood.

CLEAN UP: Water flush equipment, shrubbery, sidewalks, blacktop, asphalt, and other adjacent surfaces immediately upon contact. Leave job site free of any trace amounts of Super Bio Strip™ or dissolved residue. Never leave behind any containers or equipment. Label appropriate containers of residue for disposal.

AVAILABILITY: Available through distributors and dealers across the United States and Canada.

NOTICE: The information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY: This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES: ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING: Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our website at www.abrp.com or e-mail ABRP, Inc. at abrp@abrp.com.

American Building Restoration Products, Inc. • address: 9720 S. 60th St., Franklin, WI 53132

Corporate office: (414) 421-4125 • Orders ONLY: 1-800-346-7532 • fax: (414) 421-8696 • email: abrp@abrp.com • website: abrp.com

Updated: 8/25/2010 • Copyright © 2010 American Building Restoration Products, Inc.