

# Woodsman<sup>TM</sup>

## Premium Multi-Purpose Sealant

*Woodsman Multi-Purpose Sealant may be used for multiple applications in and around all types of homes. When used on the outside of a home this smooth surfaced sealant provides a flexible weather and water barrier that will not dry out and crack like most general purpose caulks. Woodsman adheres to most common building surfaces such as wood, metal, concrete, brick, masonry, porcelain, ceramic tile, marble and glass. Ideal for sealing construction joints like window and door frames, woodwork, eaves, soffits, vents and expansion joints, Woodsman can also be used as an internal sealant between courses of logs. Inside, Woodsman can be used for caulking / sealing around tubs, sinks, showers, etc.*

#### Coverage per 30 oz tube:

1/4 inch bead: 92 feet

3/8 inch bead: 41 feet

1/2 inch bead: 23 feet

**CAUTION! Do not take internally.  
KEEP OUT OF REACH OF CHILDREN.**

**PERMA-CHINK<sup>®</sup>**  
**SYSTEMS, INC.**

#### COLOR

- ☐ Pine
- ☐ Honey
- ☐ Tan
- ☐ Cedartone
- ☐ Brown
- ☐ Gray

#### APPLICATION DIRECTIONS

1. Surfaces must be clean, dry and free of old caulk, mold, dirt, etc. Do not apply to surfaces that are frozen or covered with ice.
2. Cut nozzle at 45° angle to desired bead size. Apply sealant with even steady pressure. For sealing gaps and joints wider than 1/2", use Backer Rod before sealing.
3. Once applied, Woodsman can be tooled smooth with a trowel, moistened sponge, brush or cloth.
4. When using as an internal sealant between courses of logs, refer to your log home manufacturer's construction manual for bead size requirements and bead location.
5. Allow 4 to 6 hours curing time, depending on weather conditions, before applying any paint or stain.
6. Apply only when surface temperatures are between 40°F and 120°F. Do not apply if rain is expected within the next 24 hours.
7. Clean hands and equipment with soap and water.

#### LIMITED WARRANTY

PERMA-CHINK SYSTEMS, Inc. warrants and represents that PERMA-CHINK SYSTEMS Family of Products will conform to the description and specifications previously set forth and shall be free from defects in material and workmanship when shipped to the buyer, EXCEPT AS HEREIN EXPRESSLY STATED. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE. APPLICABLE TO THE PERMA-CHINK LOG HOME PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Distributed By:

**Schroeder Log Home Supply, Inc.**

**1-800-359-6614    [www.loghelp.com](http://www.loghelp.com)**